

Advanced Materials**RenShape® 5169****FOUNDRY BOARD****DESCRIPTION :**

RenShape® 5169 board is an extremely tough, abrasion-resistant red material for CNC-machining foundry patterns and core boxes. The board is also well suited for producing tooling aids and fixtures and molds for thermoforming clear, thin-gauge thermoplastic sheet. Metal forming applications for durable RenShape® 5169 board include draw dies, low-pressure hydroforming molds, stretch forming dies, and wear-resistant inserts for RenCast® 6470 polyurethane molds. RenShape® 5169 board can be milled with hardened-steel cutters. Special features of the foundry board include:

ADVANTAGES	
	• Tough and resilient
	• Good edge definition and dimensional stability
	• High compressive and tensile strengths
	• Good impact and abrasion resistance
	• Surfaces can be polished to a high luster

ACCESSORIES	Matched Epoxy Adhesive	Polyurethane Repair Paste
	Ren-Weld® 5169	RenPatch® 5169

TYPICAL PROPERTIES*	Test Method	Test Values
Color	Visual	Red
Density, lb./ft. ³ (g/cm ³)	ASTM D-792	75 (1.2)
cu. in./lb.	ASTM D-2240	23.1
Hardness, Shore D		85
Ultimate Flexural Strength, 5% strain, psi (MPa)	ASTM D-790	14,000 (96.6)
Flexural Modulus, psi (MPa)	ASTM D-790	380,000 (2,621)
Ultimate Tensile Strength, psi (MPa)	ASTM D-638	9,000 (62.1)
Tg by DMA, °F (°C)	ASTM D-4065	206 (97)
Compressive Strength, 0.2% offset, psi (MPa)	ASTM D-695	8,800 (60.6)
Compressive Modulus, psi (MPa)	ASTM D-695	366,000 (2,524)
Izod Impact, notched, ft-lb./in	ASTM D-256	0.90
Coefficient of Thermal Expansion -22° to 86°F, in/in/°F -30° to 30°C, in/in/°C	ASTM D-3386	40.8 x 10 ⁻⁶ 73.5 x 10 ⁻⁶

* Tested @ 77°F (25°C) unless otherwise noted.

NOTE : These physical properties are reported as typical test values obtained by our test laboratory. If assistance is needed in establishing product specifications, please consult with our Product Management Department.

CONSTRUCTION TECHNIQUE :

- Cut RenShape® 5169 board on a band saw to form the required rough shape.
- Apply mixed Ren-Weld® 5169 adhesive to both sides of the cut board and laminate sections together.
- Gently clamp the structure and cure overnight at room temperature.
- Machine or carve contours of the model.

MACHINING	Roughing Speed	Roughing Feed	Finishing Speed	Finishing Feed
	1,600 RPM	70 - 140 IPM (178 - 356cm/ min.)	10,000 RPM	100 – 200 IPM (254 – 508 cm/min.)

Cutters : **Roughing** 1 in. (2.5cm) Hog Ball End Mill 4-Flute HS Steel 8% cobalt
Finishing 5/8 in (16mm) Ball End Mill 2-Flute Carbide
Depth Roughing varies from 0.25 in. to 2.5 in. (6mm to 6.35cm) with a 40% stepover
Finishing depth is 1/8 in. (3mm) leaving a 0.002 in. (0.05mm) scallop height
Blades Use carbide offset-tooth blade for faster cutting and less binding

These machining parameters are represented as starting points. Cutter type and material, spindle speed, feed rate, machine power and rigidity all affect machining results. User must determine the best parameters for specific situations.

PACKAGING :

RenShape® 5169 board is available in a limited number of standard combinations of 1 in., 2 in., 3 in., 4 in., 5 in. and 6 in. (2.5cm, 5cm, 7.6cm, 10cm, 12.7cm, 15cm) thicknesses, widths of 20 in and 24 in. (51cm, 60cm) and lengths of 30 in. and 60 in. (76.2cm, 152cm). Boards are finished on top and bottom faces and on all edges. Please contact Customer Service (800) 367-8793 for currently available options, price and availability.

STORAGE/HANDLING :

Store boards flat in original cartons at 60°F to 100°F (15°C to 38°C). In accord with good industrial practice, handle with due care. Avoid dusty conditions, use adequate ventilation. Avoid breathing dust. Avoid contact with eyes, skin, and clothing. Wash thoroughly after handling.

SHELF LIFE :

Provided this material is stored under the recommended storage condition in the original container, it will remain in useable condition for an unlimited amount of time.

CAUTION :

Huntsman Advanced Materials Americas Inc. maintains up-to-date Material Safety Data Sheets (MSDS) on all of its products. These sheets contain pertinent information that you may need to protect your employees and customers against any known health or safety hazards associated with our products. Users should review the latest MSDS to determine possible health hazards and appropriate precautions to implement prior to using this material. Copies of the latest MSDS may be requested by calling our customer service group at 800-367-8793 or emailing your request to kathy_dewey@huntsman.com.

FIRST AID !

Eyes and skin : Flush eyes with water for 15 minutes. Contact a physician if irritation persists. Wash skin thoroughly with soap and water. Remove and wash contaminated clothing before reuse.

Inhalation : Remove subject to fresh air.

Swallowing : Dilute by giving water to drink and contact a physician promptly. Never give anything to drink to an unconscious person.

KEEP OUT OF REACH OF CHILDREN

FOR PROFESSIONAL AND INDUSTRIAL USE ONLY

IMPORTANT LEGAL NOTICE

Sales of the product described herein ("Product") are subject to the general terms and conditions of sale of either Huntsman Advanced Materials LLC, or its appropriate affiliate including without limitation Huntsman Advanced Materials (Europe) BVBA, Huntsman Advanced Materials Americas Inc., or Huntsman Advanced Materials (Hong Kong) Ltd. ("Huntsman"). The following supersedes Buyer's documents.

Huntsman warrants that at the time and place of delivery all Products sold to Buyer shall conform to the specifications provided to Buyer by Huntsman.

While the information and recommendations included in this publication are, to the best of Huntsman's knowledge, accurate as of the date of publication, NOTHING CONTAINED HEREIN (EXCEPT AS SET FORTH ABOVE REGARDING CONFORMANCE WITH SPECIFICATIONS PROVIDED TO BUYER BY HUNTSMAN) IS TO BE CONSTRUED AS A REPRESENTATION OR WARRANTY OF ANY KIND, EXPRESS OR IMPLIED, INCLUDING BUT NOT LIMITED TO ANY WARRANTY OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE, NONINFRINGEMENT OF ANY INTELLECTUAL PROPERTY RIGHTS, OR WARRANTIES AS TO QUALITY OR CORRESPONDENCE WITH PRIOR DESCRIPTION OR SAMPLE, AND THE BUYER ASSUMES ALL RISK AND LIABILITY WHATSOEVER RESULTING FROM THE USE OF SUCH PRODUCT, WHETHER USED SINGLY OR IN COMBINATION WITH OTHER SUBSTANCES.

No statements or recommendations made herein are to be construed as a representation about the suitability of any Product for the particular application of Buyer or user or as an inducement to infringe any patent or other intellectual property right. Buyer is responsible to determine the applicability of such information and recommendations and the suitability of any Product for its own particular purpose, and to ensure that its intended use of the Product does not infringe any intellectual property rights.

The Product may be or become hazardous. The Buyer should obtain Material Safety Data Sheets and Technical Data Sheets from Huntsman containing detailed information on Product hazards and toxicity, together with proper shipping, handling and storage procedures for the Product, and should comply with all applicable governmental laws, regulations and standards relating to the handling, use, storage, distribution and disposal of, and exposure to the Product. Buyer shall also take all steps necessary to adequately inform, warn and familiarize its employees, agents, direct and indirect customers and contractors who may handle or be exposed to the Product of all hazards pertaining to and proper procedures for safe handling, use, storage, transportation and disposal of and exposure to the Product, and the containers or equipment in which the Product may be handled, shipped or stored.

RenPatch, RenShape, RenCast and RenWeld are registered trademarks of Huntsman LLC or an affiliate thereof in one or more countries, but not all countries.

© 2007 Huntsman Advanced Materials Americas Inc.

Main Offices :
Huntsman Corporation
10003 Woodloch Forest Dr.
The Woodlands
Texas 77380
(281) 719-6000

**Huntsman Advanced Technology
Center**
8600 Gosling Rd.
The Woodlands
Texas 77381
(281) 719-7400